



P/N LEGEND

A3962	HA-XP	N	2	N	NP	N	S1	G	
①	②	③	④	⑤	⑥	⑦	⑧	⑨	⑩

① Series No.
 ② Connector type: HA=Vertical
 ③ No. of circuits
 ④ N=Halogen Free
 ⑤ Material: 2=Nylon 66-V2
 ⑥ Color: N=Natural(Translucent)
 ⑦ Plating code : NP=Non-plated
 ⑧ Plating code: N=Non-plating
 ⑨ Option code: S1=S1 Type
 ⑩ Packing code: G=Bag

SPECIFICATIONS

Current Rating: 7A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Material: Nylon 66,UL94V-2
 Color: Natural(Translucent)

Ordering Information & Dimensions

PART NO.	Dimensions		
	A	B	C
02P	3.96	9.06	10.43
03P	7.92	13.02	14.39
04P	11.88	16.98	18.35
05P	15.84	20.94	22.31
06P	19.80	24.90	26.27
07P	23.76	28.86	30.23
08P	27.72	32.82	34.19
09P	31.68	36.78	38.15
10P	35.64	40.74	42.11
11P	39.60	44.70	46.07
12P	43.56	48.66	50.03

				燦達電子工業股份有限公司 JOINT TECH ELECTRONIC IND. CO., LTD.	
UNIT		SCALE	SHEET		TITLE:
mm		1 : 1	1 of 1		
DRAWN BY		APPROVED BY		3.96mm PITCH HOUSING	
周傑亮		謝瑞清			
2013.01.03		2013.01.03		DRAW NO. : A3962HA-XP2N2NPN51G	
GENERAL TOLERANCE					
X. X±0.25		ANGLE±		REV. A0	
X. XX±0.15					
X. XXX±0.05					
A0	NEW RELEASE	2013.01.03	周傑亮		
REV.	DESCRIPTION	DATE	NAME		